



# Fawori Gypsum Primer

## PRODUCT DESCRIPTION

Ready-to-use, special emulsion resin-based, transparent interior primer.

## SPECIFICATIONS

Fawori Transparent Primer forms a bridge between the paint and the surface. Enables the top-coat paint layer to integrate with the application surface by penetrating deep into the application surface with this high penetration ability. Prevents the paint to dry early especially during hot weather conditions and decreases paint consumption by preventing surface absorption. Prevents surface absorption on plaster surfaces that are challenging for the painters and prepares the surface for painting.

## APPLICATION SURFACES

Applied on plaster, lime whitewash, low quality absorbent plastic painted surfaces that lost their quality, and highly absorbing and/or high dust generating surfaces like aerated concrete.

## APPLICATION

Ensure that the application surface is smooth, firm and able to bear the primer and top-coat paint. Clean all types of stain, dust, block grease, loose layers and make the required surface corrections. Observe the setting period (28 days) for concrete, exposed concrete and new plastered surfaces.

Apply the transparent primer on plaster or similar surfaces only after they are sanded and dusted with a moist cloth/moist car wash brush/broom. Ensure the ambient and surface temperature is between +5°C and +30°C during the application and until the product is fully dry, and protect the surfaces against frost. Apply Fawori Transparent Primer as a single coat using a brush or a roller without combing/polishing (by moving the roller in one direction once) in a way that will not create a glassy thin film layer on the surface. Dull the surface with sandpaper if a glassy surface is formed. Avoid airless spraying method.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

## WARNING

Transparent Primers: Apply Fawori Transparent Primer on absorbing interior surfaces and high dust generating surfaces like plaster, lime, whitewash and aerated concrete (interior-exterior) as a single coat without combing and polishing. A glassy surface will be formed when you apply these primers to the old painted (water-solvent painted) surfaces without high dust generation and surfaces with glue / paste. Coverage, cracking and/or adherence issues can be seen on such surfaces even though you apply the top coat 7-8 times. In such a case, continue sanding and scraping until the glassy layer is fully removed.

Pigment Primers: Use Fawori Interior Transformation Primer as primer/transition primer on wall surfaces that are both primed and painted with water-solvent based paints. Since the binder will be absorbed when such primers are applied to the absorbing and high dust generating surfaces like plaster, lime, whitewash and aerated concrete, there will be a dusty appearance and other problems on the surface.

Pasted Surfaces: Apply transparent primers without combing or polishing (by rolling the roller downwards just for one turn) on absorbing and high dust generating surfaces like plaster, lime, whitewash and aerated concrete if the wall surfaces will be corrected with a paste. Then Apply the ready-to-use paste (the surface must be leveled with a paste that is compatible with bottom and top coat paint), continue with a pigment primer and move on to the final coat of paint. Notch the surface frequently if plaster is to be applied on the old paint. Otherwise, avoid applying plaster directly on paint. If applied, the final paint coat will fall along with the plaster.

Lime and Loose Layer Cleaning: Clean the old paint layers that cannot hold themselves and absorbing surfaces like lime under the paint using a wire brush, scraper and/or spiral. Or clean using a water jet with maximum 250 bar pressure after testing. Do not forget to make a sample test for water jet or sanding methods. Otherwise, high pressure may damage the surfaces and lead to significant repair and correction needs.

## THINNING

Ready to use

**DRYING TIME (at 20°C, 65% RH)**

Touch dry: 1 hour Paint application: 6 hours

(Drying time may increase at higher relative humidity and lower temperature values).

**CONSUMPTION**

Depending on the type, absorbency and structure of the application surface, an area of 8-12.5 m can be primed with 1 liter in a single coat. Perform a controlled sample run to estimate the precise consumption amount.

**STORAGE**

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

**PACKAGE**

20 L, 5 L

**WARNING STATEMENT**

Caution

**HAZARD STATEMENT**

H317 May cause an allergic skin reaction.

**PRECAUTIONARY STATEMENTS**

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Pose No.**

25.024/1,25.048/2, 25.048/3, 25.048/3A, 25.048/3B, 25.048/3C, 25.048/6

**Rate No.**

04,466/2

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

**This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.**

**Rev4 March 2020**