



THERMAL INSULATION PRODUCT GROUP

Fawori Decorative Coating Primer

DESCRIPTION

Fawori Decorative Coating Primer is a special acrylic copolymer emulsion-based white primer with a high level of adherence.

APPLICATION AREAS

Applied, prior to coating, onto thermal insulation systems and onto exterior and interior surfaces that may/may not have been painted.

SPECIFICATIONS

- High adherence quality.
- Creates a special retention between the application surface and **Fawori Decorative Coating Primer**.
- Prevents the dirt and stains on old surface to appear over the **Fawori Decorative Coating**.
- High coverage quality.
- Hardens the application surface.
- Reduces water absorbency of the surface. • Makes the surface homogeneous for coating.

COLOR

White

GLOSS

Matte



APPLICATION

Surfaces where Fawori Decorative Coating Primer is to be applied should be dry and free from any dirt. If the surface has been previously coated with a solvent-based paint, such surface should always be de-oxidized by rubbing. **Fawori Decorative Coating Primer** will be applied directly by a brush, a roller, or a sprayer onto interior or exterior surfaces that are either painted with emulsion-based paints or have never had any applications made before. Please mix before applying. The application surface and ambient temperatures should be kept between +5°C and +30°C. Do not apply on very hot surfaces with wind or direct sunlight. Recommended to be applied in a single coat 1 day before Fawori Decorative Coating application.

Considering the tint, maximum 5% colorant can be added to **Fawori Decorative Coating Primer** to ensure that it is suitable for the **Fawori Coating** color to be applied on.

THINNING

Fawori Decorative Coating Primer is supplied in a ready-to-use state. Can be thinned with a maximum of 5% clean water, where required.

DRYING TIME

(20°C, 65% HR): First Dry: 1 hour; Final Dry: 24 hours
Coating is applied after 24 hours.

CONSUMPTION:

The consumption of Fawori Decorative Coating Primer is 250-400 gr / m² in a single coat.

Please note that specified consumption values may vary to the surface and application conditions. Perform a controlled sample run to estimate the precise consumption.

PACKAGE

25 kg PE Pail

This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TSEN ISO 9001, TSEN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

* Please contact our technical support for details that are not provided above, since this technical sheet is based on general conditions. Otherwise, the manufacturer may not be held responsible for any missing information. Our company reserves the right to change the information provided. Where necessary, please refer to the Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.



STORAGE

Can be stored for 2 years in its unopened package in a cool environment protected away from frost and direct sunlight.

HAZARD STATEMENTS

H315 Causes skin irritation.

H318 Causes serious eye irritation.

PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, keep the product container or label.

P102 Keep out of the reach of children.

P103 Read label before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment required (see label).

P362 Remove your contaminated clothing and wash before reuse.

P332+P313 In case of skin irritation: Get medical advice/attention.

RATE NO.

10.300.1151

POSE NO.

15.540.1205,	15.540.1206,	15.540.1207,	15.540.1211,	15.540.1214,	15.540.1215,	15.540.1216,
15.540.1217,	15.540.1218,	15.540.1219,	15.540.1220,	15.540.1221,	15.540.1222,	15.540.1232,
15.540.1233,	15.540.1234,	15.540.1301,	15.540.1302,	15.540.1303,	15.540.1310,	15.540.1313,
15.540.1401,	15.540.1402,	15.540.1403,	15.540.1404,	15.540.1405,	15.540.1406,	15.540.1407,
15.540.1408,	15.540.140					

This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TSEN ISO 9001, TSEN ISO 14001, TS 18001, TSEN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

* Please contact our technical support for details that are not provided above, since this technical sheet is based on general conditions. Otherwise, the manufacturer may not be held responsible for any missing information. Our company reserves the right to change the information provided. Where necessary, please refer to the Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.