



TSEK

THERMAL INSULATION PRODUCT GROUP

Fawori Dowels

DESCRIPTION

Used to fix the Fawori Thermal Insulation Plates onto the surfaces in Fawori Thermal Insulation Systems and to protect the system against wind vacuum.

APPLICATION

Make holes in accordance with the diameter of the dowel with a drill. Place the dowel inside the hole in a way that it is adjacent to the insulation plate and drive a plastic or steel nail depending on the surface type.

CONSUMPTION

On average, 6 dowels are used per m² provided that one dowel is placed at each corner joint of the thermal insulation plate and two in the center.

FAWORİ STANDARD DOWEL (WITH PLASTIC NAIL)

Used in concrete, solid bricks, perforated bricks, gas concrete, and solid and perforated blocks made of light concrete.

Depth of fastening	: ≥3 cm, Depth of hole: ≥4 cm
Diameter of drill	: 10mm (Perforated Surface) -12mm (Solid Surface)
Diameter of dowel head	: 6 cm, Dowel Length: 9.5 / 11.5 / 13.5 / 15.5 cm
Package	: 600 units



RATE NO. : 10.330.2356

POSE NO.: 15.335.1001, 15.335.1002, 15.335.1003, 15.335.1004, 15.335.1005, 15.335.1006, 15.335.1101, 15.335.1102, 15.335.1103, 15.335.1104, 15.335.1105, 15.335.1106, 15.335.1201, 15.335.1202, 15.335.1203, 15.335.1204, 15.335.1205, 15.335.1206

FAWORİ CONCRETE DOWEL (WITH STEEL NAIL)

Used in concrete, exposed concrete, tunnel concrete, solid bricks, and solid and perforated blocks made of light concrete.

Depth of fastening	: >3 cm, Depth of hole: > 4 cm
Diameter of drill	: 8,0 mm on perforated surface, 9,0 mm on solid surface
Diameter of dowel head	: 6 cm, Dowel Length: 9.5 / 11.5 / 13.5 / 15.5 cm
Package	: 200 units



RATE NO. : 10.330.2351

POSE NO.: 15.340.1001, 15.340.1002, 15.340.1003, 15.340.1004, 15.340.1005, 15.340.1006

FAWORİ STONEWOOL DOWEL (WITH STEEL NAIL)

Provides perfect grip by expanding the pressure area with its 9 cm wide head diameter in external thermal insulation systems and rockwool plate applications. Used in concrete, solid bricks, perforated bricks, gas concrete, and solid and perforated blocks made of light concrete.

Depth of fastening	: >6.45 cm, Depth of hole: > 7.45 cm
Diameter of drill	: 8,0 mm on perforated surface, 9,0 mm on solid surface
Diameter of dowel head	: 9 cm, Dowel Length: 11.5 / 13.5 / 15.5 cm
Package	: 200 units



FAWORİ STONEWOOL DOWEL STAMP

Can be used with all dowels in thermal insulation plate applications, in exterior thermal insulation systems. Provides excellent grip by extending compression area of the dowel:



This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TS EN ISO 9001, TS 50001, TS ISO 10002, TS ISO/IEC 27001.

* Please contact our technical support for details that are not provided above, since this technical sheet is base manufacturer may not be held responsible for any missing information. Our company reserves the right to cl
necessary, please refer to the Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

EN ISO

vise, the
. Where



Diameter of dowel head : 9 cm
Package : 200 units

This product is manufactured by Betek A.Ş.,with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

* Please contact our technical support for details that are not provided above, since this technical sheet is based on general conditions. Otherwise, the manufacturer may not be held responsible for any missing information. Our company reserves the right to change the information provided. Where necessary, please refer to the Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.