



Fawori Paste

PRODUCT DESCRIPTION

Acrylic copolymer based, with high filling power, white-colored wood paste.

SPECIFICATIONS

Fawori Paste FW has a high filling power, holds on to the surface well, offers ease of sanding and dries fast.

APPLICATION SURFACES

Especially formulated for wood surfaces and can be used as filling or surface leveling paste on previously painted and/or plastered surfaces before paint application.

APPLICATION

Can be used on previously painted but not very dirty wood surfaces without the need of priming. Saturate the wood surfaces to be painted for the first time with 1 coat of natural wood protector before paste application. It is recommended to use sandpaper with 220 grit or more to smooth the surface. Apply with a Paste FW spatula. Ready to use. Use water for cleaning the application tools.

Note: Apply a suitable primer before Fawori Paste FW in case of application surfaces other than wood.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

THINNING

Ready to use

DRYING TIME (at 20°C, 65% RH)

Dries approximately in 2 hours depending on application thickness, humidity and temperature (drying time can increase at higher relative humidity and lower temperature values).

CONSUMPTION

Depending on the surface and the stripping-filling thickness, an area of approximately 1-1.4 m can be pasted with 1 kilogram. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 1 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

1100 g

WARNING STATEMENT

Caution

HAZARD STATEMENT

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

**This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.
Rev4 March 2020**

BETEK BOYA VE KİMYA SAN. A.Ş.

Headquarters: Zümrütevler Mahallesi Ural Sokak No:38 34852 Maltepe- İSTANBUL
Phone: (0216) 571 11 00 Fax: +90 (216) 571 13 15 – Central Registration System Number: 0167001238900018 -